

1. Pass 100Lbs super linear static thrust test.
2. Available for 12VDC /24VDC.
3. Energy saving with ultra-low-power design.
4. No residual magnetic design with stable performance.
5. Surface mounting or flush mounting for wall and floor.
6. Available for glass door with bracket.

Surface-mounted Door Holder



Model: VAL-G110

Version: Fail-unlocked
 Holding Force: 50kg(100Lbs)
 Lock Status Sensors: NO
 Surface finish: Paint and Zinc plated
 Magnets Dimensions: 70L*43W*86H(mm)
 Armature Plate Dimensions: 65L*65W*53H(mm)
 Weight in kg: 0.9kg



Model: VAL-G120

Version: Fail-unlocked
 Holding Force: 50kg(100Lbs)
 Lock Status Sensors: NO
 Surface finish: Paint and Zinc plated
 Magnets Dimensions: 80L*80W*40H(mm)
 Armature Plate Dimensions: 65L*65W*53H(mm)
 Weight in kg: 0.9kg



Model: VAL-G120

Version: Fail-unlocked
 Holding Force: 50kg(100Lbs)
 Lock Status Sensors: NO
 Surface finish: Paint and Zinc plated
 Magnets Dimensions: 80L*80W*110H(mm)
 Armature Plate Dimensions: 65L*65W*53H(mm)
 Weight in kg: 1.0kg

Floor-mounted Door Holder



Model: VAL-G150

Version: Fail-unlocked
 Holding Force: 50kg(100Lbs)
 Lock Status Sensors: NO
 Surface finish: Paint and Zinc plated
 Magnets Dimensions: 118L*93W*112H(mm)
 Armature Plate Dimensions: 65L*65W*53H(mm)
 Weight in kg: 1.4kg



Model: VAL-G160

Version: Fail-unlocked
 Holding Force: 50kg(100Lbs)
 Lock Status Sensors: NO
 Surface finish: Paint and Zinc plated
 Magnets Dimensions: 80L*80W*120H(mm)
 Armature Plate Dimensions: 65L*65W*53H(mm)
 Weight in kg: 1.05kg

