

Network Proximity Access Control

Achieve a high level of automation and modernization of access control security access attendance monitoring professional management.

Access control interface electric lock, door sensor, exit button, alarm, door bell

Network RFID Two-Door Access Control Keypad & Time Attendance



Model: VAL-2100
 Display Screen: with 122*32mm LED display screen
 Users Capacity: 2500
 Record Capacity: 25000
 Communication: RS232/485
 With Wiegand 26 port
 Dimension: 120*88*18mm
 Gross Weight: 0.25kg

Keypad network access controller



Model: VAL103
 Display Screen: B & W LCD Screen
 Authentication: ID card, Password
 Users Capacity: 30,000
 Record capacity: 50,000
 Communication: TCP/IP, RS232/485, USB-host
 Wiegand Signal Output and Input
 RF Card: ID Card or Mifare
 Dimension: 129.5*95*48.5mm
 Gross Weight: 1.25kg

Network Access Control



Model: VAL100
 Authentication: ID card, Password
 Users Capacity: 30,000
 Record capacity: 50,000
 Communication: TCP/IP, RS232/485, USB-host
 Wiegand Signal Output and Input
 Dimension: 153*95.5*35.5mm
 Gross Weight: 0.85kg

Digital Keypad

Easy operation, simple programming convenient use and reliable quality makes Digital Keypad Access Control a perfect choice for applications in office, real estates, factories etc.

Access Control Keypad
Model: VAL-260

User Code Combinations: 1 common user password, 250 multiple password for individual users.
 Access Control Interface: Electric lock, Door sensor, Exit button, alarm, DoorBell.
 Dimensions: 117Lx74Wx40D(mm)
 Weight: 0.24kg



Access Proximity Card Reader

Metal Access Card Reader

Standard Functions: Buzzer, Double color LED
 Output Format: Wiegand 26(default)/34, RS485/232 can be customized

Model: VAL-RF210
 Index of Protection: IP65
 NK-RF210EM: EM-ID 125kHz
 NK-RF210MF: Mifare IC 13.56MHz
 Material: Metal
 Size: 120*56*18(mm)
 Weight: 0.52kg



Model: VAL-RF220
 Index of Protection: IP65
 NK-RF220EM: EM-ID 125kHz
 NK-RF220MF: Mifare IC 13.56MHz
 Material: Metal
 Size: 120*80*25(mm)
 Weight: 0.54kg



Access Proximity Card Reader

Access Card Reader with keypad

Material: ABS+PC Index of Protection: IP65
Reading Range: 5~15CM Standard Functions: Buzzer, Double color LED
RFID Card Type: EM-ID 125kHz or Mifare IC 13.56MHz
Output Format: Wiegand 26(default)/WG34, RS485/232 can be customized.



Model: VAL-RF08
Size: 114*76*16(mm)
Weight: 0.21kg



Model: VAL-RF140
Size: 86*86*18(mm)
Weight: 0.21kg



Model: VAL-RF170
Size: 86*86*16.3(mm)
Weight: 0.21kg



Model: VAL-RF200
Size: 86*86*20(mm)
Weight: 0.21kg



Model: VAL-RF230
Size: 86*86*16(mm)
Weight: 0.21kg



Model: VAL-RF03
Size: 108*88*32(mm)
Weight: 0.23kg

Access Card Reader without Keypad

Material: ABS+PC Index of Protection: IP65
Reading Range: 5~15CM Standard Functions: Buzzer, Double color LED
RFID Card Type: EM-ID 125kHz or Mifare IC 13.56MHz
Output Format: Wiegand 26(default)/WG34, RS485/232 can be customized.



Model: VAL-RF01
Size: 122*46*23(mm)
Weight: 0.14kg



Model: VAL-RF02
Size: 124*76*23.5(mm)
Weight: 0.16kg



Model: VAL-RF04
Size: 119*53.1*23.2(mm)
Weight: 0.15kg



Model: VAL-RF06
Size: 88*88*10(mm)
Weight: 0.18kg



Model: VAL-RF07
Size: 76*114*16(mm)
Weight: 0.18kg



Model: VAL-RF110
Size: 86*115*18(mm)
Weight: 0.15kg



Model: VAL-RF130
Size: 86*86*18(mm)
Weight: 0.21kg



Mini Access Card Reader

Material: ABS+PC
 Index of Protection: IP65
 Reading Range: 5~15CM

Standard Functions: Buzzer, Double color LED
 RFID Card Type: EM-ID 125kHz or Mifare IC 13.56MHz
 Output Format: Wiegand 26(default)/WG34, RS485/232 can be customized.



Model: VAL-RF90S
 Size: 80*48*12.5mm
 Weight: 0.12kg



Model: VAL-RF100
 Size: 80*43*16mm
 Weight: 0.12kg



Model: VAL-RF120
 Size: 86*115*18mm
 Weight: 0.13kg



Model: VAL-RF160S
 Size: 76*45*15mm
 Weight: 0.14kg



Model: VAL-RF180
 Size: 84.5*44*16.8mm
 Weight: 0.16kg

Middle Distance Proximity Card Reader

Material: ABS+PC
 Index of Protection: IP65
 Reading Range: 70~100CM

RFID Card Type: EM-ID Middle distance card
 Standard Functions: Buzzer, Double Color LED (Red and Green)
 Output Format: Wiegand 26bits(default)/34bits, RS485/232 can be customized



Model: VAL-RF11
 Size: 230*230*35(mm)
 Weight: 1.5kg



Model: VAL-RF12
 Size: 230*230*35(mm)
 Weight: 1.5kg



Model: VAL-RF13
 Size: 230*230*35(mm)
 Weight: 1.5kg

HID series Access Card Reader

Read range of up to 15cm for proximity card and 5cm for Mifare card.
 External LED control and External Buzzer Control.
 Indoor/Outdoor operation. Waterproof IP64 or IP65.

Output Format: Wiegand 26(default)/34, RS485/232 can be customized
 Card Type: HID



Model: VAL-RF90S-HID
 Reading Range: 5-375px
 Communication Distance: WG<100M,
 RS485<1200M
 Dimension: 80*48*12.5(mm)
 Weight: 0.12kg



Model: VAL-08V-HID
 Reading Range: 5-375px
 Communication Distance: WG<100M,
 RS485<1200M
 Dimension: 48*102*215(mm)
 Weight: 0.12kg



Model: VAL-08W-HID
 Reading Range: 5-375px
 Communication Distance: WG<100M,
 RS485<1200M
 Dimension: 86*86*10(mm)
 Weight: 0.12kg

